




PIRRO

CEILING SURFACE




p. 195




E




J



K



B




2.0

2x LED 4.5W | 220-240VAC
50-60Hz | COB 3-step | incl. PS
phase-cut dim | aluminium
powder coated | PC reflector

0.30kg IP20 \varnothing 0.3° \varnothing 32°

CODE	
	151251E_
	151251J_
	151251K_
	151251B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	2x380 >90	3
3000K	2x405 >90	5




4.0

4x LED 4.5W | 220-240VAC
50-60Hz | COB 3-step | incl. PS
phase-cut dim | aluminium
powder coated | PC reflector

0.48kg IP20 \varnothing 0.3° \varnothing 32°

CODE	
	151451E_
	151451J_
	151451K_
	151451B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	4x380 >90	3
3000K	4x405 >90	5



6.0

6x LED 4.5W | 220-240VAC
50-60Hz | COB 3-step | incl. PS
phase-cut dim | aluminium
powder coated | PC reflector

0.80kg IP20 \varnothing 0.3° \varnothing 32°

CODE	
	151651E_
	151651J_
	151651K_
	151651B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	6x380 >90	3
3000K	6x405 >90	5

available from summer 2020