






DEEP IP44

CEILING RECESSED



1.0 LED

LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.32kg | IP44 | 0.3° | 36°

90

wire springs 86-89 4-25

CODE	
112661W_	112661B_

blade springs 86-89 min 8

CODE	
112661W_C	112661B_C

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480/640	>90	3
3000K	510/690	>90	5
1800-2850K 16V	300/400	>95	9

ALWAYS USE

power supply | 500mA

CODE	
10W	90214405
15W dim	90224501
20W DALI	90244602

350mA power supplies on page 694

1.0 MR16

QR-CBC51 max. 12W | GU5.3
12V | excl. power supply
aluminium powder coated

0.26kg | IP44 | 0.3° | 6°

90

wire springs 86-89 4-25

CODE	
112610W0	112610B0

blade springs 86-89 min 8

CODE	
112610W0C	112610B0C

ALWAYS USE

power supply | 12V

CODE	
10W dim	90221401
25W dim	90221701
10W dim	90221904

more specs on page 699

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.30kg | IP44 | 0.3° | 6°

105

wire springs 86-89 4-25

CODE	
112620W0	112620B0

blade springs 86-89 min 8


CODE	
112620W0C	112620B0C

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

CODE	
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701



For wireless dimming compatible with Amazon Echo Plus, Philips Hue and Homee see page 239.