



Tech Specifications




1.0

LED 11W | 220-240VAC | 50-60Hz
AC PCB 3-step low flicker
incl. PS | phase-cut dim
aluminium wet painted
red | grey | black/gold | black



2.0

LED 11W | 220-240VAC | 50-60Hz
AC PCB 3-step low flicker
incl. PS | phase-cut dim
aluminium wet painted
red | grey | black/gold | black



3.0

LED 11W | 220-240VAC | 50-60Hz
AC PCB 3-step low flicker
incl. PS | phase-cut dim
aluminium wet painted
red | grey | black/gold | black



CURIOUS?

weverducre.com/dinor

Well shaded.

Wow, what's that floating from the ceiling? We'll tell you: an LED luminaire made of ultra-thin aluminium with a minimalist design that perfectly suits contemporary interior design concepts. That's why you'll often come across DINOR in the bar or dining area of a chic restaurant, where it playfully creates stunning accents. And it comes in several different sizes and colour alternatives, such as black-gold, red-white, and grey-white. What kind of combination possibilities does DINOR offer? DINOR partners well with ROOMOR, for instance, a lighting system especially developed for the hotel sector that harmonises perfectly with the aluminium luminaire in both style and colour. See for yourself and discover the possibilities.

DINOR

Variety



1.0
red



1.0
grey



1.0
black/gold



1.0
black



2.0
red



2.0
grey



2.0
black/gold



2.0
black



3.0
red



3.0
grey



3.0
black/gold



3.0
black


WELL SHADED

DINOR



WEVER & DUCRÉ
LIGHTING





1.0

LED 11W | 220-240VAC | 50-60Hz
AC PCB 3-step low flicker
incl. PS | phase-cut dim
aluminium wet painted

0.9 kg IP20

1800-2850K | >90 CRI | 510lm

	CODE
	255189RW9
	255189GW9
	255189OK9
	255189OB9


ALWAYS USE

single ceiling base

	CODE
	90052022
	90052021

white cable on request
multi- and other suspension options
on page 608

available from autumn 2019



2.0

LED 11W | 220-240VAC | 50-60Hz
AC PCB 3-step low flicker
incl. PS | phase-cut dim
aluminium wet painted

1.3 kg IP20

1800-2850K | >90 CRI | 510lm


	CODE
	255289RW9
	255289GW9
	255289OK9
	255289OB9

ALWAYS USE

single ceiling base

	CODE
	90052022
	90052021

white cable on request
multi- and other suspension options
on page 608



3.0

LED 11W | 220-240VAC | 50-60Hz
AC PCB 3-step low flicker
incl. PS | phase-cut dim
aluminium wet painted

2.3 kg IP20

1800-2850K | >90 CRI | 510lm

	CODE
	255389RW9
	255389GW9
	255389OK9
	255389OB9

ALWAYS USE

single ceiling base

	CODE
	90052022
	90052021

white cable on request
multi- and other suspension options
on page 608