



# Tech Specifications




## IP44 1.0

LED 13W | 220-240VAC | 50-60Hz  
AC PCB 3-step low flicker  
phase-cut dim | steel wet painted opal  
PMMA cover  
white | white/gold | copper  
black/gold | black/copper | black



## IP44 2.0

LED 18W | 220-240VAC | 50-60Hz  
AC PCB 3-step low flicker  
phase-cut dim | steel wet painted opal  
PMMA cover  
white | white/gold | copper  
black/gold | black/copper | black



## IP44 3.0

LED 32W | 220-240VAC | 50-60Hz  
AC PCB 3-step low flicker  
phase-cut dim | steel wet painted opal  
PMMA cover  
white | white/gold | copper  
black/gold | black/copper | black



## More drama, please!

When the hero in the movie pulls up his collar, that's when we know: Things are about to get dramatic. And that's exactly how it is with TOWNA, whose cupped frame works like a dimmer, gently and subtly directing the light to create a warm and inviting ambience – even in smaller city apartments. TOWNA can be used both as a high-impact ceiling luminaire and as a decorative wall luminaire. A particularly practical feature: This round luminaire, inspired by nature, is available in three different sizes and six different colour options. That means it can be individually combined to suit any project.

TOWNA

# Variety



**1.0**  
black/copper



**1.0**  
black/gold



**2.0**  
black



**2.0**  
copper



**3.0**  
gold



**3.0**  
white/gold



**MORE COLOURS ON:**  
[weverducre.com/towna](http://weverducre.com/towna)

MORE DRAMA, PLEASE

# TOWNA



**WEVER & DUCRÉ**  
LIGHTING






## FORUM 1

TOWNA IP44 2019

CEILING SURFACE



### 1.0

LED 13W | 220-240VAC | 50-60Hz  
AC PCB 3-step low flicker  
phase-cut dim| steel wet painted  
opal PMMA cover

1.15kg IP44  $\approx 0,3^\circ$

	CODE
	178184W
	178184J
	178184P
	178184K
	178184Z
	178184B

#### Light Colour Selection

	LUMEN   CRI	CODE
2700K	780   >90	3
3000K	850   >90	5

#### OPTIONAL

dimmer

	CODE
for switch	90019017
for din rail	90019018

more specs on page 591



### 2.0

LED 18W | 220-240VAC | 50-60Hz  
AC PCB 3-step low flicker  
phase-cut dim| steel wet painted  
opal PMMA cover

1.90kg IP44  $\approx 0,3^\circ$

	CODE
	178284W
	178284J
	178284P
	178284K
	178284Z
	178284B

#### Light Colour Selection


	LUMEN   CRI	CODE
2700K	1090   >90	3
3000K	1210   >90	5

#### OPTIONAL

dimmer

	CODE
for switch	90019017
for din rail	90019018

more specs on page 591



### 3.0

LED 32W | 220-240VAC | 50-60Hz  
AC PCB 3-step low flicker  
phase-cut dim| steel wet painted  
opal PMMA cover

3.00kg IP44  $\approx 0,3^\circ$

	CODE
	178384W
	178384J
	178384P
	178384K
	178384Z
	178384B

#### Light Colour Selection

	LUMEN   CRI	CODE
2700K	1550   >90	3
3000K	1660   >90	5

#### OPTIONAL

dimmer

	CODE
for switch	90019017
for din rail	90019018

more specs on page 591

available from autumn 2019