



1.0

LED 6W | 220-240VAC
50-60Hz | PCB 3-step
phase-cut dim | incl. PS
aluminium powder coated
opal PMMA diffuser

0.15kg IP20 3-0.3-1

CODE	
	370184B_
	370184K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	350	>90	3
3000K	380	>90	5

2.0

LED 12W | 220-240VAC
50-60Hz | PCB 3-step
phase-cut dim | incl. PS
aluminium powder coated
opal PMMA diffuser

0.18kg IP20 3-0.3-1

CODE	
	370284B_
	370284K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	700	>90	3
3000K	760	>90	5

3.0

LED 12W | 220-240VAC
50-60Hz | PCB 3-step
phase-cut dim | incl. PS
aluminium powder coated
opal PMMA diffuser

0.30kg IP20 3-0.3-1

CODE	
	370384B_
	370384K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	700	>90	3
3000K	760	>90	5

4.0

LED 12W | 220-240VAC
50-60Hz | PCB 3-step
phase-cut dim | incl. PS
aluminium powder coated
opal PMMA diffuser

0.20kg IP20 3-0.3-1

CODE	
	370484B_
	370484K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	700	>90	3
3000K	760	>90	5

available from autumn 2020