

June

Design by Emiliana Design Studio.

Reference

4770.

Application

Outdoor lamps

Installation type

Surface

Description

Design by Emiliana Design Studio. Outdoor June path light can be installed with surface punch. It has a luminous sphere that houses LED light. June comes in matt dark brown lacquer.

Diffuser

Polycarbonate diffuser

Materials

Sphere: opal blown glass

Diffuser: Polycarbonate


Vertical tube: Steel

Finish



4770-54 Matt dark-brown lacquer (Pantone Black U)

Sketch



Electrical characteristics

1 x LED 1W 350mA



A++

Total 1.0 W

VIBIA



Light source: 2700K CRI >80 122 lm 122 lm/W

Driver included: CC - Constant Current 350 mA 100~240V 50/60Hz

Electronic dimming NO DIMMING

Technical characteristics

- Wet location
- Spike

Physical characteristics

1 Box / 0.20 x 0.18 x 1.55 m. / Vol. 0.0545 m³ /

Gross weight 3.8 kg. / Net weight 1.8 kg.


Installation and assembly

Please, see the installation manual

Light distribution

Ground lighting

Reduced-height outdoor lamp to shade light on the ground.



Photometric data

Efficiency : 24.30 lm/W

Coordinate system : CG

Total flux : 55.42 lm

Maximum value : 5.80 cd



Light position : C=90.00 G=87.50

Symmetry on the planes : Asymmetric

Isolux : (floor)

Light position :

X=0.00m Y=0.00m Z=3.00m



Certificates



June

Design by Emiliana Design Studio.

Reference

4775.

Application

Outdoor lamps

Installation type

Surface

Description

Design by Emiliana Design Studio. The June outdoor path light can be installed with surface punch. It has two luminous spheres that house LED light. June comes in matt dark brown lacquer.

Diffuser

Polycarbonate diffuser

Materials

Sphere: opal blown glass

Diffuser: Polycarbonate


Vertical tube: Steel

Finish



4775-54 Matt dark-brown lacquer (Pantone Black U)

Sketch



Electrical characteristics

2 x LED 1W 350mA



A++

Total 2.0 W

VIBIA



Light source: 2700K CRI >80 243 lm 122 lm/W

Driver included: CC - Constant Current 350 mA 100~240V 50/60Hz

Electronic dimming NO DIMMING

Technical characteristics

- Wet location
- Spike

Physical characteristics

1 Box / 0.18 x 0.20 x 1.55 m. / Vol. 0.0545 m³ /

Gross weight 4.0 kg. / Net weight 1.7 kg.


Installation and assembly

Please, see the installation manual

Light distribution

Ground lighting

Reduced-height outdoor lamp to shade light on the ground.



Photometric data

Efficiency : 25.50 lm/W

Coordinate system : CG

Total flux : 116.30 lm

Maximum value : 92.98 cd/klm



Light position : C=110.00 G=87.00

Symmetry on the planes : Asymmetric

Isolux : (floor)

Light position :

X=0.00m Y=0.00m Z=3.00m



Certificates



June

Design by Emiliana Design Studio.

Reference

4780.

Application

Outdoor lamps

Description

Design by Emiliana Design Studio. The June outdoor path light can be installed recessed. It has a luminous sphere that houses LED light. June comes in matt dark brown lacquer.

Diffuser

Polycarbonate diffuser

Materials

Sphere: opal blown glass

Diffuser: Polycarbonate


Vertical tube: Steel

Finish



4780-54 Matt dark-brown lacquer (Pantone Black U)

Sketch



Electrical characteristics

1 x LED 1W 350mA



Total 1.0 W



Light source: 2700K CRI >80 122 lm 122 lm/W

Driver included: CC - Constant Current 350 mA 100~240V 50/60Hz

Electronic dimming NO DIMMING

Technical characteristics

- Built-in

Physical characteristics

1 Box / 0.26 x 0.24 x 1.50 m. / Vol. 0.0936 m³ /

Gross weight 4.5 kg. / Net weight 2.2 kg.


Installation and assembly

Please, see the installation manual

Light distribution

Ground lighting

Reduced-height outdoor lamp to shade light on the ground.



Photometric data

Efficiency : 24.30 lm/W

Coordinate system : CG

Total flux : 55.42 lm

Maximum value : 5.80 cd



Light position : C=90.00 G=87.50

Symmetry on the planes : Asymmetric

Isolux : (floor)

Light position :

X=0.00m Y=0.00m Z=3.00m



Certificates



June

Design by Emiliana Design Studio.

Reference

4785.

Application

Outdoor lamps

Description

Design by Emiliana Design Studio. The June outdoor path light can be installed recessed. It has two luminous spheres that houses LED light. June comes in matt dark brown lacquer.

Diffuser

Polycarbonate diffuser

Materials

Sphere: opal blown glass

Diffuser: Polycarbonate


Vertical tube: Steel

Finish



4785-54 Matt dark-brown lacquer (Pantone Black U)

Sketch



Electrical characteristics

2 x LED 1W 350mA



Total 2.0 W



VIBIA



Light source: 2700K CRI >80 122 lm 122 lm/W

Driver included: CC - Constant Current 350 mA 100~240V 50/60Hz

Electronic dimming NO DIMMING

Technical characteristics

- Built-in

Physical characteristics

1 Box / 0.26 x 0.24 x 1.50 m. / Vol. 0.0936 m³ /

Gross weight 5.0 kg. / Net weight 2.3 kg.


Installation and assembly

Please, see the installation manual

Light distribution

Ground lighting

Reduced-height outdoor lamp to shade light on the ground.



Photometric data

Efficiency : 25.50 lm/W

Coordinate system : CG

Total flux : 116.30 lm

Maximum value : 10.82 cd



Light position : C=75.00 G=94.00

Symmetry on the planes : Asymmetric

Isolux : (floor)

Light position :

X=0.00m Y=0.00m Z=3.00m



Certificates

