

1.0


LED 6W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.47kg IP65 0.3

CODE		
	741168W	
	741168D	
	741168B	

Light Colour Selection

	LUMEN	CRI	CODE
2700K	400	>80	2
3000K	440	>80	4



2.0


2xLED 3W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.47kg IP65 0.3

CODE		
	741148W	
	741148D	
	741148B	

Light Colour Selection

	LUMEN	CRI	CODE
2700K	2x200	>80	2
3000K	2x220	>80	4



3.0


LED 6W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.53kg IP65 0.3

CODE		
	741268W	
	741268D	
	741268B	

Light Colour Selection

	LUMEN	CRI	CODE
2700K	400	>80	2
3000K	440	>80	4



4.0

2xLED 3W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.53kg IP65 0.3

CODE		
	741248W	
	741248D	
	741248B	

Light Colour Selection

	LUMEN	CRI	CODE
2700K	2x200	>80	2
3000K	2x220	>80	4

RAY
OUTDOOR
WALL SURFACE

