




# MATCH

TRIMLESS | CEILING RECESSED



## 1.0 TRIMLESS

LED COB 6W | 350mA | 18V  
excl. driver  
aluminium powder coated

IP20 0°-90°/350° 25° SDCM2 L80|50K 0.15kg

45-47 85 4-26

CODE	
	190851W_
	190851B_


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480	>90	3
3000K	510	>90	5

## ALWAYS USE

driver | 350mA

CODE	
10W dim	90223402
10W DALI	90243401

more options and specs on page 724



## 1.0

LED COB 6W | 350mA | 18V  
excl. driver  
aluminium powder coated

IP20 0°-90°/350° 25° SDCM2 L80|50K 0.14kg

wire springs 45-47 85 4-26

CODE	
	190151W_
	190151H_
	190151B_


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480	>90	3
3000K	510	>90	5

## ALWAYS USE

driver | 350mA

CODE	
10W dim	90223402
10W DALI	90243401

more options and specs on page 724



## 2.0

2x LED COB 6W | 700mA | 18V  
excl. driver  
aluminium powder coated

IP20 0°-90°/350° 25° SDCM2 L80|50K 0.27kg

wire springs 105x30 60 4-26

CODE	
	190251W_
	190251B_


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x480	>90	3
3000K	2x510	>90	5

## ALWAYS USE

driver | 700mA | only 1x needed

CODE	
15W dim	90225502
28W DALI	90245801

more options and specs on page 727



IC rated



289



325



533