





DEEP ADJUST

CEILING RECESSED



2.0 LED

2x LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated
1800-2850K 16V

0.61kg IP20 0.3-1D 36°
35°/35° 355° 90 86-89x172-178
4-23

	CODE
	112761W_
	112761B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x530/710	>90	3
3000K	2x570/770	>90	5
4000K	2x580/800	>90	6
1800-2850K	2x330/450	>95	9

ALWAYS USE

power supply | 500mA

	CODE
10W	90214405
15W dim	90224501
20W DALI	90244602

350mA power supplies on page 694

2.0 PAR16

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.42kg IP20 0.3-1D 35°/35°
355° 105 86-89x172-178
4-23

	CODE
	112720W0
	112720B0

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701



For wireless dimming compatible
with Amazon Echo Plus, Philips Hue
and Homee see page 239.